

# מדחום דיגיטלי ללא מגע יד אדם



<b>Accuracy</b>	±0.2 degrees	Response time	0.5s
<b>Abnormal automatic alarm</b>	flashing + "Di Di" sound	Charging method	USB charging or battery
<b>Automatic measurement</b>	measuring distance 5cm - 10cm	Input	USB DC 4.2-5V
<b>Standby</b>	About one week	Weight	350g
<b>Install method</b>	nail hook, double-sided adhesive sticking, bracket fixing	Dimensions	170*115*140mm
<b>Operating temperature</b>	10C-40C (Recommend 15°C~35°C)	Infrared measuring range	0~50°C
<b>Standby</b>	5s (Red dot dynamic cycle)	Screen	Digital display

**Approved by CE**, The EMC Directive 2014/30/EU, EN 55032: 2015, EN 55035: 2017 EN 61000-3-2: 2014, EN 61000-3-3: 2013

The Medical Directive 93/42/EEC, EN 60601-1 :2006+A1 :2013+A 11 :2011 +A 12:2014; EN 60601-1-2:2015,

**Approved by FCC** LSC EMC-1.0 - Conducted disturbance at mains terminals: FCC Part 15, Subpart B, Class B(sDoC), ANSI C63.4 -201

**Class B PASS** & Radiated disturbance: FCC Part 15, Subpart B, Class B(sDoC), ANSI C63.4 -2014

**Approved by The RoHS** Directive 2011/65/EU and its amendment directives 2015/863/EU - IEC 62321-3-1:2013 IEC 62321-5:2013

IEC 62321-4:2013+AMD1:2017 CSV - IEC 62321-6:2015 IEC 62321-7-1:2015 IEC 62321-7-2:2017 IEC 62321-8:2017